

Projects:

Comments:

Superchip[™] Exclusive 50 Watt Syncable Color-Changing LED Flood Light

| SPECIFICATIONS: | | |
|-----------------------------|--|--------------------------------------|
| POWER USED: | 50 Watts | |
| MODEL #: | FLRW5 | |
| | 0 | |
| LISTINGS | CE RoHS, TUV, FCC | t bart er. T ba Flab Flat Flab |
| VOLTAGE: | 90VAC ~277VAC | F als F als F als F als |
| POWER FACTOR: | >0.95 | A A La A A A |
| FREQUENCY: | >0.95 50-60Hz 5,000 Lumens 100 Lm/W 2700K to 6500K White + DCD | |
| LUMENS: | 5,000 Lumens | |
| LUMENS EFFICACY: | 100 Lm/W | IP65 |
| KELVIN (CCT): | 2700K to 6500K White + RGB | |
| COLOR SPECTRUM: | 16 Million Colors (RGB) + White | |
| CRI: | >80 | |
| IP RATING: | IP65 Outdoor / Wet Location Use | |
| BEAM ANGLE (DEGREE): | 160° Wide or 25° Narrow | 160° MODEL |
| MOUNTING: | U-Bracket (Rocket Post Optional) | 100 WODLE |
| MATERIALS: | Heavy Duty Cast Aluminum & Tempered Glass Lens | |
| USED FOR: | Commercial / Residential Landscapes | |
| APPLICATIONS: | Wall Washing, General Floodlighting, Etc. | 100 |
| LIFE SPAN (HOURS): | 50,000+ Hours | |
| DIMMING COMPATIBLE: | Dimmable (with controller) | ender of the |
| LENGTH OF WARRANTY (YEARS): | 3 years | 000000 |
| WORKING ENVIRONMENT: | -15°F to +120°F | Ball Store |
| RELAY ABILITY: | Signal can relay from light to light up to 100' | A COLOUSE ! |
| 1.87″ 8.66″ | Signal can relay from light to light up to 100' | IP65 |



FCCCE





