



Projects:

Comments:

## Superchip<sup>™</sup> Exclusive 6 Watt Syncable Color-Changing LED Spot Light

| SPECIFICATIONS:             |  |              |
|-----------------------------|--|--------------|
| POWER USED:                 | 6 Watts                                      |              |
| MODEL #:                    | SBRW1  |              |
|                             |  |              |
| LISTINGS                    | CE RoHS, TUV, FCC                            |              |
| VOLTAGE:                    | 90VAC ~277VAC                                |              |
| POWER FACTOR:               | >0.95  |              |
| FREQUENCY:                  | 50-60Hz                                      |              |
| LUMENS:                     | 550 Lumen                                    | Superchip    |
| LUMENS EFFICACY:            | 95 Lm/W                                      |              |
| KELVIN (CCT):               | 2700K to 6500K White + RGB                   |              |
| COLOR SPECTRUM:             | 16 Million Colors (RGB) + White              |              |
| CRI:                        | >80  |              |
| IP RATING:                  | IP66 Outdoor / Wet Location Use              |              |
| BEAM ANGLE (DEGREE):        | 25°  |              |
| MOUNTING:                   | U-Bracket + In-Ground Spike (Rocket Pos      | st Optional) |
| MATERIALS:                  | Heavy Duty Cast Aluminum & Tempered          | Glass Lens   |
| USED FOR:                   | Commercial / Residential Landscapes          |              |
| APPLICATIONS:               | Column, Tree, Flag Pole Uplighting, etc.     |              |
| LIFE SPAN (HOURS):          | 50,000+ Hours                                |              |
| DIMMING COMPATIBLE:         | Dimmable (with controller)                   |              |
| LENGTH OF WARRANTY (YEARS): | 3 years                                      |              |
| WORKING ENVIRONMENT:        | -15°F to +120°F                              | V            |
| RELAY ABILITY:              | Signal can relay from light to light up to 2 | 100'         |





4.33"

FCCCE

